



FS-EX1080-G

Northstar Classic 80' Cable SRL

**Features and Benefits**

Class B SRL
Swivel attachment point
High-strength polymer housing
Integrated carrying handle

3/16" galvanized steel cable
Steel carabiner attachment
LI swivel snap hook

Length of Cable

80 ft (24.4 m)

Weight of Unit

26.6 lbs (12.1 kg)

Hook Ratings

5,000 lbs (2267.96 kg) Tensile Strength
3,600 lbs (1632 kg) Gate Rated

Maximum Arresting Force

<1,800 lbs (816.47 kg)

Maximum Arrest Distance

<54 in (1371.6 mm)

Standards Compliant With

ANSI	Z359.14-14, A10.32
OSHA	1926.502

ANSI SRL Class

Class B

User Weight Capacity

ANSI 130-310 lbs (140.6 kg)
OSHA Up to 420 lbs (190.5 kg)

Material Specifications:

Cable	3/16" Galvanized Steel
Lifeline Connector	Forged Steel Load Indicating Swivel Snap Hook
Housing	Polymer
Housing Connector	Forged Steel Carabiner



FS-EX10-100-G

Northstar Classic 100' Cable SRL

**Features and Benefits**

Class B SRL
Swivel attachment point
High-strength polymer housing
Integrated carrying handle

3/16" galvanized steel cable
Steel carabiner attachment
LI swivel snap hook

Length of Cable 100 ft (30.5 m)

Weight of Unit 32 lbs (14.5 kg)

Hook Ratings 5,000 lbs (2267.96 kg) Tensile Strength
3,600 lbs (1632 kg) Gate Rated

Maximum Arresting Force <1,800 lbs (816.47 kg)

Maximum Arrest Distance <54 in (1371.6 mm)

Standards Compliant With

ANSI	Z359.14-14, A10.32
OSHA	1926.502

ANSI SRL Class Class B

User Weight Capacity ANSI 130-310 lbs (140.6 kg)
OSHA Up to 420 lbs (190.5 kg)

Material Specifications:

Cable	3/16" Galvanized Steel
Lifeline Connector	Forged Steel Load Indicating Swivel Snap Hook
Housing	Polymer
Housing Connector	Forged Steel Carabiner